

HIGHLY EFFICIENT ENDURANCE RUNNER

Super Digital Inverter R32



Symbol photo



Highlights

- Highly efficient, compact & quiet
- Wide operating temperature range
- Twin-rotary compressor



Super Digital Inverter outdoor unit with refrigerant R32 for cooling or heating with a wide performance spectrum. Available in five capacities from 5.3 to 14.0 kW.



Performance

- Suitable for 24/7 continual operation
- Very good energy efficiency values (up to A+++)
- SEER values up to 9.40 possible depending on the combination
- SCOP values up to 5.52 possible depending on the combination
- Exceptionally high efficiency in the partial load range
- Controls at the lowest, min. capacities
- Corresponds to the ECODESIGN Lot 10 Directive



Flexibility

- Max. pipe lengths up to 75 m
- Max. height differences up to 30 m
- Wide operating temperature range from -27 to +52 °C
- Optimal ratio of unit capacity to installation surface



Technical details

- Direct current hybrid inverter technology
- Twin-rotary compressor
- Kit available for noise reduction & power limitation
- Energy monitoring for single-phase systems with RBC-AMS55E

Super Digital Inverter R32

Technical data			RAV-GP1101AT-E
Cooling capacity	kW	❄️	10,00
Outdoor temperature operating range (min.-max.)	°C	❄️	-15/+52
Heating capacity	kW	🔥	11,20
Outdoor temperature operating range (min.-max.)	°C	🔥	-27/+15
Sound pressure level (low/med/high)	dB(A)	❄️	49
Sound pressure level (low/med/high)	dB(A)	🔥	50
Sound pressure level (night operation)	dB(A)		44/45
Sound power level	dB(A)	❄️	66
Sound power level	dB(A)	🔥	67
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		5
Pipe length (max.)	m		75
Height difference (max.)	m		30
Airflow	m ³ /h		6960
Power supply	V/Ph+N/Hz		220-240/1N/50
Recommended fusing	A		20
Current consumption (nom.)	A		11,0
Current consumption (max.)	A		22,8
Recommended power supply line type			H07RN-F 3G4,0
Communication line			H07RN-F 4G1,5
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		3,10
Pre-charged up to	m		30
Added refrigerant charge	g/m		35
Dimensions (HxWxD)	mm		1550 x 1010 x 370
Weight	kg		104

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.