

COMPACT ENTRY-LEVEL MODEL

Seiya



Highlights

- Modern compact inverter
- A++ in cooling mode
- Infrared remote control included – WiFi ready



The SEIYA entry-level model offers all the efficiency advantages of inverter technology combined with a rotary compressor. Set consists of an outdoor and indoor unit, using refrigerant R32.



Attractive & economical

- Excellent energy efficiency (A+ to A++)
- Direct current hybrid inverter technology
- Rotary compressor in sizes 07 to 18
- Twin-rotary compressor in size 24
- Exceptionally high efficiency in the partial load range
- Colored, dimmable LED displays



Resource-friendly & quiet

- Minimal electricity consumption due to inverter control
- Eco operating mode
- Low GWP refrigerant R32
- Air used as energy source during heating operation
- Compact outdoor and indoor units
- "Quiet" whisper mode for indoor units
- "Silent" whisper mode for outdoor units



Clean ambient air

- Washable dust filter that covers the entire heat exchanger
- "Dustless coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Optional active carbon-catechin filter strips (art.818F0023)



Easy operation

- Infrared remote control included
- WiFi ready
- Optional app control via smartphone or tablet
- OFF timer
- Automatic mode
- Hi Power
- Quiet and silent modes
- Louver swing & fix
- Automatic restart after power blackout
- Cooling-only & heating-only settings
- Defrosting on demand



WiFi special features

- All indoor units & groups on/off control
- All indoor units & groups weekly timer
- All indoor units & groups setting
- Indoor temperature display
- Outdoor temperature display
- Quiet function for indoor unit
- Power select
- Child lock
- On/off timer
- 8°C function
- ECO operating mode
- Silence function for outdoor unit
- Fireplace operating mode
- Hi Power operating mode

Seiya / SET

Indoor unit	RAS-B10J2KVG-E		
Outdoor unit	RAS-10J2AVG-E		
Cooling capacity	kW	❄️	2,50
Cooling range (min.-max.)	kW	❄️	0,80 - 3,00
Power consumption (min./nom./max.)	kW	❄️	0,24/0,77/1,00
Pdesign c	kW		2,50
Energy efficiency EER	W/W	❄️	3,25
Energy efficiency SEER		❄️	6,10
Energy efficiency class		❄️	A++
Annual electricity consumption	kWh/a	❄️	143
Outdoor temperature operating range (min.-max.)	°C	❄️	-15/+46
Heating capacity	kW	🔥	3,20
Heating range (min.-max.)	kW	🔥	1,00 - 3,90
Power consumption (min./nom./max.)	kW	🔥	0,20/0,86/1,11
Pdesign h	kW		2,40
Energy efficiency COP	W/W	🔥	3,72
Energy efficiency SCOP		🔥	4,00
Energy efficiency class		🔥	A+
Annual electricity consumption	kWh/a	🔥	839
Outdoor temperature operating range (min.-max.)	°C	🔥	-15/+24

Indoor unit	RAS-B10J2KVG-E		
Sound pressure level (low/med/high)	dB(A)	❄️	21/32/39
Sound pressure level (low/med/high)	dB(A)	🔥	21/32/39
Sound power level	dB(A)	❄️	54
Sound power level	dB(A)	🔥	54
Airflow	m ³ /h		240 - 552
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		293 x 798 x 230
Weight	kg		9

❄️ Cooling 🔥 Heating

Seiya / SET

Outdoor unit			RAS-10J2AVG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		10
Current consumption (max.)	A		7,2
Sound pressure level (low/med/high)	dB(A)	❄️	48
Sound pressure level (low/med/high)	dB(A)	🔥	49
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	65
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		15
Height difference (max.)	m		12
Airflow	m ³ /h		1800
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,43
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		530 x 660 x 240
Weight	kg		23

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.