TOSHIBA

1:1 SINGLE-SPLIT OUTDOOR UNIT R32

SHORAI EDGE





Compact and quiet outdoor units with low-GWP refrigerant R32 for 1:1 combination with SHORAI EDGE or CONSOLES indoor units. In a robust, weatherproof housing, can be set up flexibly.

Economical & reliable

- Very high energy efficiency (A +++)
- DC hybrid inverter technology
- Single (07 to 16) or twin rotary compressor (18 to 24)
- Particularly high efficiency in part load range
- Complies with the ECODESIGN Lot10 guideline
- Wide operating temperature range
- Housing made of galvanized sheet steel with a creamcolored stove enamel finish
- Large curved heat exchanger for a small footprint
- Automatic restart after power failure adjustable

Saving resources

- Inverter control minimizes power consumption
- Eco mode
- Environmentally friendly low-GWP refrigerant R32 prefilled
- Air as an energy source in heating mode
- Inconspicuous design adapts to any environment
- SILENT whisper mode

Comfort and economy functions

- Operation via comfort IR remote control (included with the indoor unit)
- Clear & simple operation
- Automatic mode
- Hi power
- Comfort sleep
- Weekly timer with 4 freely programmable settings / day
- 28 time programs per week
- SILENT operating mode
- 8 ° C frost protection function
- Power Select
- Optional APP control via smartphone and tablet



TOSHIBA

SHORAI EDGE / SET

Indoor unit			RAS-B07J2KVSG-E
Outdoor unit			RAS-07J2AVSG-E
Cooling capacity	kW	*	2,00
Cooling range (minmax.)	kW	*	0,89 - 2,90
Power consumption (min./nom./max.)	kW	*	0,19/0,39/0,67
Pdesign c	kW		2,00
Energy efficiency EER	W/W	*	5,13
Energy efficiency SEER		*	8,50
Energy efficiency class		*	A+++
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	۲	2,50
Heating range (minmax.)	kW	۲	0,90 - 3,60
Power consumption (min./nom./max.)	kW	۲	0,16/0,50/0,80
Pdesign h	kW		2,30
Energy efficiency COP	W/W	۲	5,00
Energy efficiency SCOP		۲	5,10
Energy efficiency class		۲	A+++
Outdoor temperature operating range (minmax.)	°C	۲	-15/+24

Indoor unit			RAS-B07J2KVSG-E
Sound pressure level (low/med/high)	dB(A)	*	19/22/40
Sound pressure level (low/med/high)	dB(A)	۲	19/23/40
Sound power level	dB(A)	*	53
Sound power level	dB(A)	۲	53
Airflow	m³/h		660
Dimensions (HxWxD)	mm		293 x 800 x 226
Weight	kg		10

🕸 Cooling 🛛 뵽 Heating

TOSHIBA

SHORAI EDGE / SET

Outdoor unit			RAS-07J2AVSG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		10
Sound pressure level (low/med/high)	dB(A)	*	44
Sound pressure level (low/med/high)	dB(A)	*	46
Sound power level	dB(A)	*	53
Sound power level	dB(A)	*	59
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
iquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m³/h		1890
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,55
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		26

🗱 Cooling ` 🗮 Heating

The measuring conditions for this product can be found at http://www.toshiba-klima.at/en/measuring-conditions.html

OSHIBA

TOSHIBA Features - general overview



Energy Label: Energy label A+ to A+++, indicates the power consumption and energy efficiency class.



ErP Ecodesign: All criteria of ECODESIGN-guideline are fulfilled and confirm highest system efficiency.



Hybrid inverter control: Smooth capacity regulation.



Rotary compressor: Reliability and high efficiency.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R410A: Used refrigerant: R410A.



R32: Used refrigerant: R32.



Wifi ready: Optional control of the system via a smartphone.



KNX: Optional KNX bus connection.



Dust filter: Washable filter against coarse contamination.



IAQ filter: Fine mesh filter with natural substances.



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Plasma filter: Pure Mode: Electrostatic filter system.



Air ionizer: Negative iones cover polluted particles in the air. Dust, pollen and smoke are neutralized.



Self-cleaning function: Usage of condensate water for cleaning.



Auto Mode: Automatic selection between cooling and heating.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Auto diagnostic: Check of system for flawless operation.



Eco Mode: Energy saving function.



Quiet Mode: Particularly low noise level - whispering mode.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



ব

Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



Floor Mode: Natural floor warming effect for greater comfort.



Preset Mode: Activates individual settings at the touch of a button.



One Touch Mode: Fully automatic operation adapted to your needs.



Timer: Individual programming of on-/off times.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Week Timer: Up to four settings per day and seven per week.



Automatic Restart: After a power blackout.



8 °C frost protection function: Frost protection for uninhabited rooms.



3D ~J||L> Louver: Flexible setting of louvers.



3D Airflow: 6 different airflow patterns in all directions.



