



2-pipe powerhouse next generation

SMMS-u

→ Highlights

- Pointing the way in connectivity, efficiency, reliability and service friendliness
- Single modules up to 24 HP / 67 kW cooling capacity available
- Combinations of up to 335 kW cooling- and 345 kW heating-capacity
- Unique triple-rotary compressor (16-20 HP)

VRF 2-pipe outdoor unit for cooling or heating operation with a wide performance spectrum. For combination with VRF indoor units, DX-kits, hot water modules and VN heat exchangers according to the Selection Tool design software.

→ Performance

- SEER values up to 7,73
- SCOP values up to 4,79
- Optimized R410A refrigeration circuit enables the smallest amount of refrigerant
- Outstanding energy and cost efficiency
- Suitable for monovalent heating operation
- Hi-Power fan unit optimizes the airflow
- Super efficient split heat exchanger
- Defrosting in heating mode without sacrificing comfort
- Maximum operational reliability through auto backup

→ Flexibility

- Maximum piping lengths up to 1,200 m (from 26 HP)
- Maximum height differences up to 110 m
- Up to 128 indoor units can be connected to each individual system
- Capacities up to 24 HP available with just one outdoor unit module
- Combinations of up to 120 HP / 335 kW cooling capacity possible
- Free combination concept, according to priority efficiency or installation space
- Flexible control options for all applications
- Night Operation: quiet operation protects humans and the environment
- System diversity up to 200%
- Easy system design with SelectionTool software
- Combination with existing systems possible

→ Technical details

- Perfected A3 twin-rotary compressor (8-14 HP)
- Two A3 twin-rotary compressors (22-24 HP)
- Unique K4 triple-rotary compressor (16-20 HP)
- Double-vane technology with carbon coating
- Auto-Backup operation
- Uninterrupted heating operation for up to 5 hours
- Ultra-short defrosting cycles of up to 3.5 minutes
- Intelligent refrigerant management ensures the best possible supply for all indoor units, regardless of their position in the building
- Shortest oil return cycles thanks to intelligent oil management algorithms
- Fast TU2C-Link system bus with 19,200 bps
- The wireless NFC WaveTool function simplifies commissioning, service and system monitoring with Android smartphones
- The DynaDoctor service tool for convenient recording, monitoring and diagnosis as a PC application can be connected to outdoor or indoor devices via USB
- Optional service link adapter TCB-SS1UU-E enables data logging even without a PC on micro SDHC card (included, 8 GB)

| Technical data | | | MMY-UP7411HT8P-E |
|---|-------------------|----|--------------------------|
| Capacity code | HP | | 74 |
| Combined units | | | 24 + 24 + 14 + 12 |
| Cooling capacity | kW | ❄️ | 207,50 |
| Power consumption (min./nom./max.) | kW | ❄️ | 73,27 |
| Energy efficiency EER | W/W | ❄️ | 2,83 |
| Energy efficiency SEER | | ❄️ | 6,97 |
| Heating capacity | kW | 🔥 | 207,50 |
| Power consumption (min./nom./max.) | kW | 🔥 | 55,73 |
| Energy efficiency COP | W/W | 🔥 | 3,72 |
| Energy efficiency SCOP | | 🔥 | 4,36 |
| Airflow | m ³ /h | | 2x 16500 + 11880 + 11700 |
| External static pressure | Pa | | 80 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 68.0 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 72.0 |
| Sound power level | dB(A) | ❄️ | 91.0 |
| Sound power level | dB(A) | 🔥 | 95.0 |
| Sound pressure level (night operation) | dB(A) | | 59,0 |
| Liquid pipe diameter | mm (inch) | | 22,2 (7/8) |
| Suction gas pipe diameter | mm (inch) | | 44,5 (1 3/4) |
| Outdoor temperature operating range (min.-max.) | °C | ❄️ | -15 / +52 |
| Outdoor temperature operating range (min.-max.) | °C | 🔥 | -25 / +15,5 |
| Power supply | V/Ph+N/Hz | | 380-415/3/50 |
| Starting current | A | | Softstart |
| Connectable indoor units (max.) | Pce. | | 86 |
| Pipe length (max.) | m | | 1200 |
| Height difference (max.) | m | | 110 |
| Refrigerant | | | R410A |
| Refrigerant charge | kg | | 9+9+6+6 |
| Dimensions (HxWxD) | mm | | 1690 x 4620 x 780 |
| Weight | kg | | 2x 356 + 2x 228 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.