



PERFECT AMBIANCE

Ceiling unit R32/R410A



Highlights

- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode

Under-ceiling unit for RAV single-room systems for combination with Digital Inverter, Super Digital Inverter, and BIG Digital Inverter outdoor units for refrigerant R32 or R410A. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in five power levels from 3.6 to 12.5 kW.



Performance

- Extremely high energy efficiency (up to A+++)
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Compatible with R32 or R410A outdoor units
- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Easy installation via removable suspension fixtures
- Optional TCB-DP31CE drain pump available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC link
- Automatic restart setting after power outage
- Optional redundancy box available

TOSHIBA

Ceiling unit R32/R410A

Technical data			RAV-GM901CTP-E
Cooling capacity	kW	❄️	8,00
Cooling range (min.-max.)	kW	❄️	1,90 - 8,80
Energy efficiency EER	W/W	❄️	3,10
Energy efficiency SEER		❄️	6,10
Energy efficiency class		❄️	A++
Heating capacity	kW	🔥	9,00
Heating range (min.-max.)	kW	🔥	1,6 - 9,90
Energy efficiency COP	W/W	🔥	3,40
Energy efficiency SCOP		🔥	4,60
Energy efficiency class		🔥	A++
Sound pressure level (low/med/high)	dB(A)	❄️	30/38/42
Sound pressure level (low/med/high)	dB(A)	🔥	30/38/42
Sound power level	dB(A)	❄️	15/53/57
Sound power level	dB(A)	🔥	15/53/57
Airflow	m ³ /h		900/1600
Condensate pipe diameter	mm		VP20 (20/26)
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Communication line			H07RN-F 4G1,5
Refrigerant			R32
Dimensions (HxWxD)	mm		235 x 1586 x 690
Weight	kg		37

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.