




PREMIUM SINGLE-SPLIT

Daiseikai 9 - R32



Highlights

- Maximum energy efficiency A+++
- "Wooden texture reflect" finish in white
- "Fireplace" operating mode
- Two "silent" modes for the outdoor unit



Daiseikai 9 combines design with comfort and the ultimate in efficiency. Both outdoor and indoor units combine flawless operation with timeless design and the very best air filter system.



Attractive and economical

- Highest energy efficiency (A+++)
- SEER values up to 10.6
- Direct current hybrid inverter technology
- Twin-rotary compressor
- Exceptionally high efficiency in the partial load range
- Single installation
- Colored, dimmable LED displays
- Draft-free comfort due to 3D air distribution
- Stylish wooden texture reflect surface



Resource-friendly

- Inverter control minimizes electricity consumption
- Eco operation
- Air used as energy source in heating mode
- Unobtrusive design fits any interior
- Compact & quiet outdoor unit



Cleaner ambient air

- Washable dust filter that covers the entire heat exchanger
- Special coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Plasma filter
- SUPER ionizer
- Optional active carbon-catechin filter strips (art.818F0023)
- Optional IAQ filter strips (art.818F0036)



Easy operation

- Comes with comfort infrared remote control as standard
- Clear & easy operation
- Large, backlit display
- Weekly timer with 4 freely programmable settings per day
- 28 time programs per week
- 8°C frost protection function
- Power Select
- Automatic mode
- Eco mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- 3D airflow with 6 air flow patterns
- Automatic restart setting after power outage
- Cooling-only & heating-only settings
- Optional WiFi control via smartphone, tablet, or PC
- Fireplace operating mode uses heat from other sources
- Silent mode reduces outdoor unit sound pressure by up to 4 dB(A)

Daiseikai 9 - R32 / SET

Indoor unit	RAS-13PKVPG-E		
Outdoor unit	RAS-13PAVPG-E		
Cooling capacity	kW	❄️	3,50
Cooling range (min.-max.)	kW	❄️	0,90 - 4,10
Power consumption (min./nom./max.)	kW	❄️	0,18/0,75/1,00
Pdesign c	kW		3,50
Energy efficiency EER	W/W	❄️	4,67
Energy efficiency SEER		❄️	9,50
Energy efficiency class		❄️	A+++
Annual electricity consumption	kWh/a	❄️	129
Outdoor temperature operating range (min.-max.)	°C	❄️	-15/+46
Heating capacity	kW	🔥	4,00
Heating range (min.-max.)	kW	🔥	0,80 - 6,30
Power consumption (min./nom./max.)	kW	🔥	0,17/0,80/2,00
Pdesign h	kW		3,60
Energy efficiency COP	W/W	🔥	5,00
Energy efficiency SCOP		🔥	5,10
Energy efficiency class		🔥	A+++
Annual electricity consumption	kWh/a	🔥	988
Outdoor temperature operating range (min.-max.)	°C	🔥	-15/+24

Indoor unit	RAS-13PKVPG-E		
Sound pressure level (low/med/high)	dB(A)	❄️	20/34/45
Sound pressure level (low/med/high)	dB(A)	🔥	20/34/45
Sound power level	dB(A)	❄️	59
Sound power level	dB(A)	🔥	60
Airflow	m ³ /h		710
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		293 x 851 x 270
Weight	kg		14

❄️ Cooling 🔥 Heating

Daiseikai 9 - R32 / SET

Outdoor unit			RAS-13PAVPG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		10
Current consumption (nom.)	A		3,39
Current consumption (max.)	A		3,73
Sound pressure level (low/med/high)	dB(A)	❄️	48
Sound pressure level (low/med/high)	dB(A)	🔥	50
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	65
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		25
Height difference (max.)	m		10
Airflow	m ³ /h		2160
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,00
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 800 x 300
Weight	kg		43

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.