



High output flexibility

2-way cassette



Highlights

- Wide performance spectrum
- Quiet operation
- External fresh air supply possible



2-way cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Perfectly suited for long, narrow spaces. Available in eleven power levels from 2.2 to 16.0 kW.



Performance

- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage

2-way cassette

| Technical data | | | MMU-AP0152WH1 |
|-------------------------------------|-----------|----|-----------------|
| Cooling capacity | kW | ❄️ | 4,50 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,03 |
| Heating capacity | kW | 🔥 | 5,00 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,03 |
| Airflow | m³/h | | 600 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 30/33/35 |
| Liquid pipe diameter | mm (inch) | | 6,4 (¼) |
| Suction gas pipe diameter | mm (inch) | | 12,7 (½) |
| Condensate pipe diameter | mm | | VP25 (25/32) |
| Power supply | V/Ph+N/Hz | | 220-240/1/50 |
| Running current | A | ❄️ | 0,24 |
| Running current | A | 🔥 | 0,24 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 295 x 815 x 570 |
| Weight | kg | | 19 |
| Panel dimensions (HxWxD) | mm | | 20 x 1050 x 680 |
| Panel weight | kg | | 10 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Hybrid inverter control: Smooth capacity regulation.



Rotary compressor: Reliability and high efficiency.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R410A: Used refrigerant: R410A.



R32: Used refrigerant: R32.



Wifi ready: Optional control of the system via a smartphone.



KNX: Optional KNX bus connection.



Dust filter: Washable filter against coarse contamination.



IAQ filter: Fine mesh filter with natural substances.



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Plasma filter: Pure Mode: Electrostatic filter system.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



Self-cleaning function: Usage of condensate water for cleaning.



Auto Mode: Automatic selection between cooling and heating.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Auto diagnostic: Check of system for flawless operation.



Eco Mode: Energy saving function.



Quiet Mode: Particularly low noise level - whispering mode.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



Floor Mode: Natural floor warming effect for greater comfort.



Preset Mode: Activates individual settings at the touch of a button.



One Touch Mode: Fully automatic operation adapted to your needs.



Timer: Individual programming of on-/off times.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Week Timer: Up to four settings per day and seven per week.



Automatic Restart: After a power blackout.



8 °C frost protection function: Frost protection for uninhabited rooms.



Louver: Flexible setting of louvers.



3D Airflow: 6 different airflow patterns in all directions.